

Haynesville Shale Sand Specs

Company Name	Region	Mining Location	Mesh size	Crush Resistance - K Factor	Specific Gravity	Bulk Density (lb/ft3)	Bulk Density (g/cm3)	Krumbein Roundness	Krumbein Sphericity	Acid Solubility (wt %)	Turbidity (FTU)	Conductivity (MD-FT)						Permeability (DARCY)					
												20000 psi	4000 psi	6000 psi	8000 psi	10000 psi	12000 psi	2000 psi	4000 psi	6000 psi	8000 psi	10000 psi	12000 psi
Performance Proppants, LLC	Bossier Parish County	Bossier City, LA	100 M	-	-	-	-	-	-	-	-	--	-	-	-	-	-	-	-	-	-	-	-
	Miller County	Doddridge, AR	40/70	6K	-	-	-	-	-	-	-	--	-	-	-	-	-	-	-	-	-	-	-
			100 M	7K	-	-	-	-	-	-	-	--	-	-	-	-	-	-	-	-	-	-	-
U.S. Silica	Smith County	Tyler, TX	40/70	-	-	-	-	-	-	-	-	--	-	-	-	-	-	-	-	-	-	-	-
			100 M	-	-	-	-	-	-	-	-	--	-	-	-	-	-	-	-	-	-	-	-
Sierra Frac Sand	Bossier Parish County	Benton, LA	40/70	-	-	-	-	-	-	-	-	--	-	-	-	-	-	-	-	-	-	-	-
			100 M	-	-	-	-	-	-	-	-	--	-	-	-	-	-	-	-	-	-	-	-
			16/30	-	-	-	-	-	-	-	-	--	-	-	-	-	-	-	-	-	-	-	-
			20/40	-	-	-	-	-	-	-	-	--	-	-	-	-	-	-	-	-	-	-	-
			30/50	-	-	-	-	-	-	-	-	--	-	-	-	-	-	-	-	-	-	-	-
			30/70	-	-	-	-	-	-	-	-	--	-	-	-	-	-	-	-	-	-	-	-
SamSand	Miller County	Garland City, AR	-	-	-	-	-	-	-	-	-	--	-	-	-	-	-	-	-	-	-	-	-

Note: Data sourced from company websites.